

## NORFAB Series 400 Cloth 17pt31

A Norfab woven medium fabric of an Aramid fiber blend over a fiberglass core yarn. Applications include safety clothing, curtains, heat shields, filtration cloth and rubberized hose. Resistant to reflected heat sources, offers excellent thermal protection for safety garments.

## **About NOR\*FAB Corporation**

NOR\*FAB manufactures textile products using flame resistant synthetic fibers suited for use at high temperatures and for personal protection. These items include broad woven roll goods and narrow products in the form of woven and knitted tapes, sleeving, rope, and gasketing. NOR\*FAB uses para-aramid, meta-aramid, melamine, phenolic, oxidized PAN, flame resistant rayon, polybenzimideazole, and other technical fibers blended into unique yarns which provide high levels of heat protection and insulation.

NOR\*FAB produces many of these yarns on the DREF Spinning System for use in the weaving, knitting, gasket, and wire & cable industries. NOR\*FAB possesses the largest collection of DREF III spinning frames of any yarn manufacturer in the world.

## Among its offerings, NOR\*FAB boasts fabric lines for the following end uses:

Firefighting

OMNI Vantage<sup>™</sup>, OMNI Elite<sup>®</sup>, OMNI 45<sup>™</sup>, and OMNI Quilt<sup>™</sup> Electric Arc Protection NF Arc<sup>™</sup>, ArcWeld<sup>®</sup> Welding Protection ArcWeld<sup>®</sup> Cut Protection CutPro<sup>®</sup>



## **NORFAB Series 400 Data Sheet** Style 17PT31 Base Fabric Aramid/Fiberglass Color/Appearance Yellow Plain Style Fa

Fabric Weight, oz./sq yd, average	17 (577 gm/sq.m)
Fabric Thickness, inches	0.080 (2.05 mm)
Warp Strength, lbs/in.	200.0 (90 Kg/2.54 cm)
Fill Strength, lbs/in.	75.0 (34 Kg/2.54 cm)
Abrasion Resistance	Excellent
Available Finishes	
Finish Number	• 00, Loom Stage;

• See Fabric Finish Options data sheet



1310 Stanbridge Street, Box 830, Norristown, PA 19404-0830 U.S.A. Tel: 610-275-7270 • 800-441-9680 • Fax: 610-277-6106 Email: sales@norfab.com • www.norfab.com